

WebDT Signage Appliance

SA1000/ SA2000/ SA3000 Comparison Chart



Comparison:

Model	SA1000	SA2000	SA3000
System			
Processor	1.5GHz x86 processor	AMD Sempron™ 1.6GHz/ 2GHz, or AMD Turion™ 2.1GHz Dual-Core processor	Intel® Core™ 2 Duo processor, 2.26 GHz
RAM	1GB (DDR II SODIMM x 1)	1GB or 2GB (DDR II SODIMM x 1)	Up to 2GB (DDR II SODIMM x 1)
Storage	4GB, 8GB, or 16GB Flash	4GB, 8GB or 16GB Flash, or 120GB HDD	4G, 8G or 16GB Industrial Flash or 2.5" SATA SSD/ HDD (Optional)
Display	Up to 1920 x 1080		
Operating System	Microsoft® Windows® XP Embedded		
Wireless Connection	10/100 BaseT LAN/ WiFi 802.11a/b/g		
I/O Ports			
Video In	N/A	S-video input x 1, Composite input x 1	N/A
Video Out	DVI-I x 1	VGA x 1 / HDMI x 1	VGA x 1 / HDMI x 1
Audio Jack	3.5mm phone jack x 3	3.5mm phone jack x 3	3.5mm phone jack x 2
USB	2	2	2
Serial Port	N/A	RS232 x 1	RS232 x 1
Ethernet	RJ45 connector for Ethernet x 1		
DC In	1		
Optional ports	WiFi Dipole antenna x 1		
Power			
AC/DC Adapter	Input: 100-240V Output: 12VDC	Input: 100-240V Output: 18.5VDC	Input: 100-240V Output: 18.5VDC
Power Cords	North America, EU, UK, China		
Mechanical and Environmental			
Dimensions (H x W x D)	1.7" x 5.5" x 5.1"	2" x 5.5" x 6.5"	1.96" x 5.5" x 6.5"
Weight	1.2 lbs/ 544g	2.3 lbs/ 1050g	2.7lbs/ 1230g (Flash); 2.9lbs/ 1330g (HDD)
Enclosure	Aluminium	Aluminium / Iron	Aluminium / Iron
Operating Temperature	0° – 40°C		
Humidity	0% – 90% non-condensing		
Regulatory	FCC Class B, CE, C-Tick, RoHS compliant	FCC Class B, CE, C-Tick, UL, RoHS compliant	
Compatibilities			
Software Compatibility	Compatible with WCM 2.3 or above		Compatible with WCM 3.0 or above